

W1, W2, W3, W4, WR SERIES - NYLON

Ref.Number	Bore Dia	Rod Dia	Nominal Wear Ring Dimensions			
			D	H	S	
3/32" - Cross Section - 0.094"						
WR012500187-094	1.250	1.062	1.250	0.187	0.094	
WR015000187-094	1.500	1.312	1.500	0.187	0.094	
WR015000375-094	1.500	1.312	1.500	0.375	0.094	
WR020000187-094	2.000	1.812	2.000	0.187	0.094	
WR020000375-094	2.000	1.812	2.000	0.375	0.094	
WR025000375-094	2.500	2.312	2.500	0.375	0.094	
WR025501500-094	2.550	2.362	2.550	1.500	0.094	
WR028501000-094	2.850	2.662	2.850	1.000	0.094	
WR032500375-094	3.250	3.062	3.250	0.375	0.094	
WR033120625-094	3.312	3.125	3.312	0.625	0.094	
WR035000500-094	3.500	3.312	3.500	0.500	0.094	
WR035000750-094	3.500	3.312	3.500	0.750	0.094	
WR036250218-094	3.625	3.437	3.625	0.218	0.094	
WR039370218-094	3.937	3.750	3.937	0.218	0.094	
WR040000375-094	4.000	3.812	4.000	0.375	0.094	
WR050000500-094	5.000	4.812	5.000	0.500	0.094	
WR060000500-094	6.000	5.812	6.000	0.500	0.094	
3/31" - Cross Section - 0.096"						
WR030000212-096	3.000	2.808	3.000	0.212	0.096	
WR032500212-096	3.250	3.058	3.250	0.212	0.096	
WR036250212-096	3.625	3.433	3.625	0.212	0.096	
0.098" - Cross Section - 0.098"						
WR020000190-098	2.000	1.804	2.000	0.190	0.098	
WR027002280-098	2.700	2.500	2.700	2.280	0.098	
WR029501970-098	2.950	2.750	2.950	1.970	0.098	
WR030000990-098	3.000	2.800	3.000	0.990	0.098	
WR032001180-098	3.200	3.000	3.200	1.180	0.098	
WR032501125-098	3.250	3.050	3.250	1.125	0.098	
WR034501610-098	3.450	3.250	3.450	1.610	0.098	
WR034501970-098	3.450	3.250	3.450	1.970	0.098	
WR034502760-098	3.450	3.250	3.450	2.760	0.098	
WR037001770-098	3.700	3.500	3.700	1.770	0.098	
WR037001880-098	3.700	3.500	3.700	1.880	0.098	
WR037002360-098	3.700	3.500	3.700	2.360	0.098	
WR039502440-098	3.950	3.750	3.950	2.440	0.098	
WR040000212-098	4.000	3.800	4.000	0.212	0.098	
WR040001312-098	4.000	3.800	4.000	1.312	0.098	
WR042001312-098	4.200	4.000	4.200	1.312	0.098	
WR042001570-098	4.200	4.000	4.200	1.570	0.098	
WR042002560-098	4.200	4.000	4.200	2.560	0.098	

Ref.Number	Bore Dia	Rod Dia	Nominal Wear Ring Dimensions			
			D	H	S	
0.098" - Cross Section - 0.098"						
WR044502360-098	4.450	4.250	4.450	2.360	0.098	
WR047001970-098	4.700	4.500	4.700	1.970	0.098	
WR049501970-098	4.950	4.750	4.950	1.970	0.098	
WR052002520-098	5.200	5.000	5.200	2.520	0.098	
WR054502500-098	5.450	5.250	5.450	2.500	0.098	
WR059501970-098	5.950	5.750	5.950	1.970	0.098	
WR059503620-098	5.950	5.750	5.950	3.620	0.098	
WR062001960-098	6.200	6.000	6.200	1.960	0.098	
WR067002270-098	6.700	6.500	6.700	2.270	0.098	
WR072003150-098	7.200	7.000	7.200	3.150	0.098	
WR074502360-098	7.450	7.250	7.450	2.360	0.098	
WR077003122-098	6.700	6.500	6.700	3.122	0.098	
WR082002950-098	8.200	8.000	8.200	2.950	0.098	
WR099502950-098	9.950	9.750	9.950	2.950	0.098	
1/10" - Cross Section - 0.100"						
WR092003000-100/BZ	9.200	9.000	9.200	3.000	0.100	
1/8" - Cross Section - 0.125"						
W2010000375	1.000	0.750	1.000	0.375	0.125	
W2010000500	1.000	0.750	1.000	0.500	0.125	
W2010000625	1.000	0.750	1.000	0.625	0.125	
W2011250375	1.125	0.875	1.125	0.375	0.125	
W2011250500	1.125	0.875	1.125	0.500	0.125	
W2012500250	1.250	1.000	1.250	0.250	0.125	
W2012500375	1.250	1.000	1.250	0.375	0.125	
W2012500500	1.250	1.000	1.250	0.500	0.125	
W2012500625	1.250	1.000	1.250	0.625	0.125	
W2012500750	1.250	1.000	1.250	0.750	0.125	
W2012501000	1.250	1.000	1.250	1.000	0.125	
W2013750500	1.375	1.125	1.375	0.500	0.125	
W2013750750	1.375	1.125	1.375	0.750	0.125	
W2013751000	1.375	1.125	1.375	1.000	0.125	
W2015000250	1.500	1.250	1.500	0.250	0.125	
W2015000375	1.500	1.250	1.500	0.375	0.125	
W2015000500	1.500	1.250	1.500	0.500	0.125	
W2015000625	1.500	1.250	1.500	0.625	0.125	
W2015000750	1.500	1.250	1.500	0.750	0.125	
W2015001000	1.500	1.250	1.500	1.000	0.125	
W2016250375	1.625	1.375	1.625	0.375	0.125	
W2016250442	1.625	1.375	1.625	0.442	0.125	
W2016250500	1.625	1.375	1.625	0.500	0.125	

NOTE: MINIMUM LINE ORDER MAY APPLY

W1, W2, W3, W4, WR SERIES - NYLON

INCH SIZE
GUIDING ELEMENTS



Ref.Number	Bore Dia	Rod Dia	Nominal Wear Ring Dimensions			
			D	H	S	
1/8" - Cross Section - 0.125"						
W2017500250	1.750	1.500	1.750	0.250	0.125	
W2017500375	1.750	1.500	1.750	0.375	0.125	
W2017500500	1.750	1.500	1.750	0.500	0.125	
W2017500625	1.750	1.500	1.750	0.625	0.125	
W2017500750	1.750	1.500	1.750	0.750	0.125	
W2017501000	1.750	1.500	1.750	1.000	0.125	
W2018750500	1.875	1.625	1.875	0.500	0.125	
W2018750750	1.875	1.625	1.875	0.750	0.125	
W2018751000	1.875	1.625	1.875	1.000	0.125	
W2020000160	2.000	1.750	2.000	0.160	0.125	
W2020000250	2.000	1.750	2.000	0.250	0.125	
W2020000312	2.000	1.750	2.000	0.312	0.125	
W2020000375	2.000	1.750	2.000	0.375	0.125	
W2020000500	2.000	1.750	2.000	0.500	0.125	
W2020000625	2.000	1.750	2.000	0.625	0.125	
W2020000750	2.000	1.750	2.000	0.750	0.125	
W2020001000	2.000	1.750	2.000	1.000	0.125	
W2020001250	2.000	1.750	2.000	1.250	0.125	
W2020001500	2.000	1.750	2.000	1.500	0.125	
W2021250375	2.125	1.875	2.125	0.375	0.125	
W2021250500	2.125	1.875	2.125	0.500	0.125	
W2021250750	2.125	1.875	2.125	0.750	0.125	
W2021870260	2.187	1.937	2.187	0.260	0.125	
W2021871000	2.187	1.937	2.187	1.000	0.125	
W2022500187	2.250	2.000	2.250	0.187	0.125	
W2022500250	2.250	2.000	2.250	0.250	0.125	
W2022500312	2.250	2.000	2.250	0.312	0.125	
W2022500375	2.250	2.000	2.250	0.375	0.125	
W2022500500	2.250	2.000	2.250	0.500	0.125	
W2022500625	2.250	2.000	2.250	0.625	0.125	
W2022500750	2.250	2.000	2.250	0.750	0.125	
W2022500875	2.250	2.000	2.250	0.875	0.125	
W2022500890	2.250	2.000	2.250	0.890	0.125	
W2022501000	2.250	2.000	2.250	1.000	0.125	
W2022501250	2.250	2.000	2.250	1.250	0.125	
W2022501500	2.250	2.000	2.250	1.500	0.125	
W2023750500	2.375	2.125	2.375	0.500	0.125	
W2023750750	2.375	2.125	2.375	0.750	0.125	
W2025000160	2.500	2.250	2.500	0.160	0.125	
W2025000187	2.500	2.250	2.500	0.187	0.125	
W2025000250	2.500	2.250	2.500	0.250	0.125	
W2025000312	2.500	2.250	2.500	0.312	0.125	
W2025000375	2.500	2.250	2.500	0.375	0.125	
W2025000500	2.500	2.250	2.500	0.500	0.125	
W2025000625	2.500	2.250	2.500	0.625	0.125	
W2025000740	2.500	2.250	2.500	0.740	0.125	
W2025000750	2.500	2.250	2.500	0.750	0.125	
W2025000875	2.500	2.250	2.500	0.875	0.125	
W2025001000	2.500	2.250	2.500	1.000	0.125	
W2025001250	2.500	2.250	2.500	1.250	0.125	
W2025001500	2.500	2.250	2.500	1.500	0.125	
W2026250500	2.625	2.375	2.625	0.500	0.125	
W2026250625	2.625	2.375	2.625	0.625	0.125	
W2026250750	2.625	2.375	2.625	0.750	0.125	
W2026251000	2.625	2.375	2.625	1.000	0.125	
W2027500250	2.750	2.500	2.750	0.250	0.125	
W2027500312	2.750	2.500	2.750	0.312	0.125	
W2027500375	2.750	2.500	2.750	0.375	0.125	
W2027500500	2.750	2.500	2.750	0.500	0.125	
W2027500625	2.750	2.500	2.750	0.625	0.125	
W2027500750	2.750	2.500	2.750	0.750	0.125	
W2027500940	2.750	2.500	2.750	0.940	0.125	
W2027501000	2.750	2.500	2.750	1.000	0.125	
W2027501500	2.750	2.500	2.750	1.500	0.125	
W2027501750	2.750	2.500	2.750	1.750	0.125	
W2027502000	2.750	2.500	2.750	2.000	0.125	
W2028750500	2.875	2.625	2.875	0.500	0.125	
W2028750750	2.875	2.625	2.875	0.750	0.125	
W2028750875	2.875	2.625	2.875	0.875	0.125	
W2028751000	2.875	2.625	2.875	1.000	0.125	
W2030000160	3.000	2.750	3.000	0.160	0.125	
W2030000250	3.000	2.750	3.000	0.250	0.125	
W2030000312	3.000	2.750	3.000	0.312	0.125	
W2030000375	3.000	2.750	3.000	0.375	0.125	
W2030000500	3.000	2.750	3.000	0.500	0.125	
W2030000570	3.000	2.750	3.000	0.570	0.125	
W2030000625	3.000	2.750	3.000	0.625	0.125	
W2030000750	3.000	2.750	3.000	0.750	0.125	
W2030000990	3.000	2.750	3.000	0.990	0.125	
W2030001000	3.000	2.750	3.000	1.000	0.125	
W2030001250	3.000	2.750	3.000	1.250	0.125	
W2030001500	3.000	2.750	3.000	1.500	0.125	
W2030001562	3.000	2.750	3.000	1.562	0.125	
W2030620250	3.062	2.812	3.062	0.250	0.125	
W2031250500	3.125	2.875	3.125	0.500	0.125	
W2031251000	3.125	2.875	3.125	1.000	0.125	
W2032500250	3.250	3.000	3.250	0.250	0.125	
W2032500312	3.250	3.000	3.250	0.312	0.125	

NOTE: MINIMUM LINE ORDER MAY APPLY

W1, W2, W3, W4, WR SERIES - NYLON

W1, W2, W3, W4, WR SERIES - NTECH						
Ref.Number	Bore Dia	Rod Dia	Nominal Wear Ring Dimensions			
			D	H	S	
1/8" - Cross Section - 0.125"						
W2032500375	3.250	3.000	3.250	0.375	0.125	
W2032500500	3.250	3.000	3.250	0.500	0.125	
W2032500625	3.250	3.000	3.250	0.625	0.125	
W2032500750	3.250	3.000	3.250	0.750	0.125	
W2032501000	3.250	3.000	3.250	1.000	0.125	
W2032501130	3.250	3.000	3.250	1.130	0.125	
W2032501250	3.250	3.000	3.250	1.250	0.125	
W2032501500	3.250	3.000	3.250	1.500	0.125	
W2032501550	3.250	3.000	3.250	1.550	0.125	
W2032501562	3.250	3.000	3.250	1.562	0.125	
W2032501625	3.250	3.000	3.250	1.625	0.125	
W2032502000	3.250	3.000	3.250	2.000	0.125	
W2032502125	3.250	3.000	3.250	2.125	0.125	
W2033750500	3.375	3.125	3.375	0.500	0.125	
W2033750750	3.375	3.125	3.375	0.750	0.125	
W2035000160	3.500	3.250	3.500	0.160	0.125	
W2035000250	3.500	3.250	3.500	0.250	0.125	
W2035000375	3.500	3.250	3.500	0.375	0.125	
W2035000437	3.500	3.250	3.500	0.437	0.125	
W2035000500	3.500	3.250	3.500	0.500	0.125	
W2035000625	3.500	3.250	3.500	0.625	0.125	
W2035000750	3.500	3.250	3.500	0.750	0.125	
W2035000875	3.500	3.250	3.500	0.875	0.125	
W2035001000	3.500	3.250	3.500	1.000	0.125	
W2035001120	3.500	3.250	3.500	1.120	0.125	
W2035001250	3.500	3.250	3.500	1.250	0.125	
W2035001500	3.500	3.250	3.500	1.500	0.125	
W2036250500	3.625	3.375	3.625	0.500	0.125	
W2036250625	3.625	3.375	3.625	0.625	0.125	
W2036250750	3.625	3.375	3.625	0.750	0.125	
W2036251000	3.625	3.375	3.625	1.000	0.125	
W2037500250	3.750	3.500	3.750	0.250	0.125	
W2037500375	3.750	3.500	3.750	0.375	0.125	
W2037500500	3.750	3.500	3.750	0.500	0.125	
W2037500625	3.750	3.500	3.750	0.625	0.125	
W2037500750	3.750	3.500	3.750	0.750	0.125	
W2037501000	3.750	3.500	3.750	1.000	0.125	
W2037501250	3.750	3.500	3.750	1.250	0.125	
W2037501490	3.750	3.500	3.750	1.490	0.125	
W2037501500	3.750	3.500	3.750	1.500	0.125	
W2037502000	3.750	3.500	3.750	2.000	0.125	
W2038750250	3.875	3.625	3.875	0.250	0.125	
W2038751000	3.875	3.625	3.875	1.000	0.125	
W2040000160	4.000	3.750	4.000	0.160	0.125	

Ref.Number	Bore Dia	Rod Dia	Nominal Wear Ring Dimensions			
			D	H	S	
1/8" - Cross Section - 0.125"						
W2040000250	4.000	3.750	4.000	0.250	0.125	
W2040000312	4.000	3.750	4.000	0.312	0.125	
W2040000375	4.000	3.750	4.000	0.375	0.125	
W2040000500	4.000	3.750	4.000	0.500	0.125	
W2040000570	4.000	3.750	4.000	0.570	0.125	
W2040000625	4.000	3.750	4.000	0.625	0.125	
W2040000710	4.000	3.750	4.000	0.710	0.125	
W2040000750	4.000	3.750	4.000	0.750	0.125	
W2040000875	4.000	3.750	4.000	0.875	0.125	
W2040000990	4.000	3.750	4.000	0.990	0.125	
W2040001000	4.000	3.750	4.000	1.000	0.125	
W2040001250	4.000	3.750	4.000	1.250	0.125	
W2040001500	4.000	3.750	4.000	1.500	0.125	
W2040002000	4.000	3.750	4.000	2.000	0.125	
W2041250420	4.125	3.875	4.125	0.420	0.125	
W2041251000	4.125	3.875	4.125	1.000	0.125	
W2042500250	4.250	4.000	4.250	0.250	0.125	
W2042500375	4.250	4.000	4.250	0.375	0.125	
W2042500500	4.250	4.000	4.250	0.500	0.125	
W2042500625	4.250	4.000	4.250	0.625	0.125	
W2042500750	4.250	4.000	4.250	0.750	0.125	
W2042500875	4.250	4.000	4.250	0.875	0.125	
W2042501000	4.250	4.000	4.250	1.000	0.125	
W2042501250	4.250	4.000	4.250	1.250	0.125	
W2042501500	4.250	4.000	4.250	1.500	0.125	
W2042501890	4.250	4.000	4.250	1.890	0.125	
w2042502000	4.250	4.000	4.250	2.000	0.125	
W2042502500	4.250	4.000	4.250	2.500	0.125	
W2042502750	4.250	4.000	4.250	2.750	0.125	
W2042600500	4.260	4.010	4.260	0.500	0.125	
W2044000625	4.400	4.150	4.400	0.625	0.125	
W2045000180	4.500	4.000	4.500	0.180	0.125	
W2045000250	4.500	4.000	4.500	0.250	0.125	
W2045000375	4.500	4.250	4.500	0.375	0.125	
W2045000500	4.500	4.250	4.500	0.500	0.125	
W2045000625	4.500	4.250	4.500	0.625	0.125	
W2045000750	4.500	4.250	4.500	0.750	0.125	
W2045000875	4.500	4.250	4.500	0.875	0.125	
W2045000930	4.500	4.250	4.500	0.930	0.125	
W2045000990	4.500	4.250	4.500	0.990	0.125	
W2045001000	4.500	4.250	4.500	1.000	0.125	
W2045001250	4.500	4.250	4.500	1.250	0.125	
W2045001500	4.500	4.250	4.500	1.500	0.125	
W2045001870	4.500	4.250	4.500	1.870	0.125	

NOTE: MINIMUM LINE ORDER MAY APPLY

W1, W2, W3, W4, WR SERIES - NYLON

INCH SIZE
GUIDING ELEMENTS



Ref.Number	Bore Dia	Rod Dia	Nominal Wear Ring Dimensions			
			D	H	S	
1/8" - Cross Section - 0.125"						
W2045002360	4.500	4.250	4.500	2.360	0.125	
W2046251000	4.625	4.375	4.625	1.000	0.125	
W2047500375	4.750	4.500	4.750	0.375	0.125	
W2047500500	4.750	4.500	4.750	0.500	0.125	
W2047500625	4.750	4.500	4.750	0.625	0.125	
W2047500750	4.750	4.500	4.750	0.750	0.125	
W2047501000	4.750	4.500	4.750	1.000	0.125	
W2047501250	4.750	4.500	4.750	1.250	0.125	
W2047501500	4.750	4.500	4.750	1.500	0.125	
W2047501562	4.750	4.500	4.750	1.562	0.125	
W2047501990	4.750	4.500	4.750	1.990	0.125	
W2047502000	4.750	4.500	4.750	2.000	0.125	
W2047503500	4.750	4.500	4.750	3.500	0.125	
W2048750375	4.875	4.625	4.875	0.375	0.125	
W2048750750	4.875	4.625	4.875	0.750	0.125	
W2050000375	5.000	4.750	5.000	0.375	0.125	
W2050000500	5.000	4.750	5.000	0.500	0.125	
W2050000625	5.000	4.750	5.000	0.625	0.125	
W2050000750	5.000	4.750	5.000	0.750	0.125	
W2050000860	5.000	4.750	5.000	0.860	0.125	
W2050000875	5.000	4.750	5.000	0.875	0.125	
W2050001000	5.000	4.750	5.000	1.000	0.125	
W2050001120	5.000	4.750	5.000	1.120	0.125	
W2050001125	5.000	4.750	5.000	1.125	0.125	
W2050001250	5.000	4.750	5.000	1.250	0.125	
W2050001500	5.000	4.750	5.000	1.500	0.125	
W2050001562	5.000	4.750	5.000	1.560	0.125	
W2050001750	5.000	4.750	5.000	1.750	0.125	
W2050002000	5.000	4.750	5.000	2.000	0.125	
W2051251562	5.125	4.875	5.125	1.562	0.125	
W2052500375	5.250	5.000	5.250	0.375	0.125	
W2052500500	5.250	5.000	5.250	0.500	0.125	
W2052500625	5.250	5.000	5.250	0.625	0.125	
W2052500750	5.250	5.000	5.250	0.750	0.125	
W2052501000	5.250	5.000	5.250	1.000	0.125	
W2052501030	5.250	5.000	5.250	1.030	0.125	
W2052501250	5.250	5.000	5.250	1.250	0.125	
W2052501500	5.250	5.000	5.250	1.500	0.125	
W2052502000	5.250	5.000	5.250	2.000	0.125	
W2052502250	5.250	5.000	5.250	2.250	0.125	
W2052503500	5.250	5.000	5.250	3.500	0.125	
W2052503620	5.250	5.000	5.250	3.620	0.125	
W2055000375	5.500	5.250	5.500	0.375	0.125	
W2055000500	5.500	5.250	5.500	0.500	0.125	
W2055000625	5.500	5.250	5.500	0.625	0.125	
W2055000750	5.500	5.250	5.500	0.750	0.125	
W2055001000	5.500	5.250	5.500	1.000	0.125	
W2055001250	5.500	5.250	5.500	1.250	0.125	
W2055001312	5.500	5.250	5.500	1.312	0.125	
W2055001370	5.500	5.250	5.500	1.370	0.125	
W2055001500	5.500	5.250	5.500	1.500	0.125	
W2055001620	5.500	5.250	5.500	1.620	0.125	
W2055001750	5.500	5.250	5.500	1.750	0.125	
W2055002000	5.500	5.250	5.500	2.000	0.125	
W2055002250	5.500	5.250	5.500	2.250	0.125	
W2057500500	5.750	5.500	5.750	0.500	0.125	
W2057500625	5.750	5.500	5.750	0.625	0.125	
W2057500750	5.750	5.500	5.750	0.750	0.125	
W2057501000	5.750	5.500	5.750	1.000	0.125	
W2057501500	5.750	5.500	5.750	1.500	0.125	
W2057501620	5.750	5.500	5.750	1.620	0.125	
W2057501750	5.750	5.500	5.750	1.750	0.125	
W2057502000	5.750	5.500	5.750	2.000	0.125	
W2057502370	5.750	5.500	5.750	2.370	0.125	
W2060000180	6.000	5.750	6.000	0.180	0.125	
W2060000250	6.000	5.750	6.000	0.250	0.125	
W2060000375	6.000	5.750	6.000	0.375	0.125	
W2060000500	6.000	5.750	6.000	0.500	0.125	
W2060000625	6.000	5.750	6.000	0.625	0.125	
W2060000630	6.000	5.750	6.000	0.630	0.125	
W2060000750	6.000	5.750	6.000	0.750	0.125	
W2060000875	6.000	5.750	6.000	0.875	0.125	
W2060001000	6.000	5.750	6.000	1.000	0.125	
W2060001070	6.000	5.750	6.000	1.070	0.125	
W2060001250	6.000	5.750	6.000	1.250	0.125	
W2060001320	6.000	5.750	6.000	1.320	0.125	
W2060001500	6.000	5.750	6.000	1.500	0.125	
W2060001740	6.000	5.750	6.000	1.740	0.125	
W2060001750	6.000	5.750	6.000	1.750	0.125	
W2060002000	6.000	5.750	6.000	2.000	0.125	
W2060002500	6.000	5.750	6.000	2.500	0.125	
W2060002860	6.000	5.750	6.000	2.860	0.125	
W2062500500	6.250	6.000	6.250	0.500	0.125	
W2062500625	6.250	6.000	6.250	0.625	0.125	
W2062500750	6.250	6.000	6.250	0.750	0.125	
W2062501000	6.250	6.000	6.250	1.000	0.125	
W2062501490	6.250	6.000	6.250	1.490	0.125	
W2062501500	6.250	6.000	6.250	1.500	0.125	

NOTE: MINIMUM LINE ORDER MAY APPLY

W1, W2, W3, W4, WR SERIES - NYLON

Ref.Number	Bore Dia	Rod Dia	Nominal Wear Ring Dimensions			
			D	H	S	
1/8" - Cross Section - 0.125"						
W2062501750	6.250	6.000	6.250	1.750	0.125	
W2062502000	6.250	6.000	6.250	2.000	0.125	
W2062502760	6.250	6.000	6.250	2.760	0.125	
W2063751240	6.375	6.125	6.375	1.240	0.125	
W2063752500	6.375	6.125	6.375	2.500	0.125	
W2065000375	6.500	6.250	6.500	0.375	0.125	
W2065000500	6.500	6.250	6.500	0.500	0.125	
W2065000625	6.500	6.250	6.500	0.625	0.125	
W2065000750	6.500	6.250	6.500	0.750	0.125	
W2065001000	6.500	6.250	6.500	1.000	0.125	
W2065001250	6.500	6.250	6.500	1.250	0.125	
W2065001370	6.500	6.250	6.500	1.370	0.125	
W2065001375	6.500	6.250	6.500	1.375	0.125	
W2065001500	6.500	6.250	6.500	1.500	0.125	
W2065001750	6.500	6.250	6.500	1.750	0.125	
W2065002000	6.500	6.250	6.500	2.000	0.125	
W2065002740	6.500	6.250	6.500	2.740	0.125	
W2065002860	6.500	6.250	6.500	2.860	0.125	
W2065002880	6.500	6.250	6.500	2.880	0.125	
W2065003500	6.500	6.250	6.500	3.500	0.125	
W2067500375	6.750	6.500	6.750	0.375	0.125	
W2067500500	6.750	6.500	6.750	0.500	0.125	
W2067500625	6.750	6.500	6.750	0.625	0.125	
W2067500750	6.750	6.500	6.750	0.750	0.125	
W2067501000	6.750	6.500	6.750	1.000	0.125	
W2067501500	6.750	6.500	6.750	1.500	0.125	
W2067561250	6.756	6.506	6.756	1.250	0.125	
W2068752000	6.875	6.625	6.875	2.000	0.125	
W2070000375	7.000	6.750	7.000	0.375	0.125	
W2070000500	7.000	6.750	7.000	0.500	0.125	
W2070000625	7.000	6.750	7.000	0.625	0.125	
W2070000687	7.000	6.750	7.000	0.687	0.125	
W2070000750	7.000	6.750	7.000	0.750	0.125	
W2070001000	7.000	6.750	7.000	1.000	0.125	
W2070001250	7.000	6.750	7.000	1.250	0.125	
W2070001500	7.000	6.750	7.000	1.500	0.125	
W2070001750	7.000	6.750	7.000	1.750	0.125	
W2070002000	7.000	6.750	7.000	2.000	0.125	
W2070002370	7.000	6.750	7.000	2.370	0.125	
W2070003000	7.000	6.750	7.000	3.000	0.125	
W2070003120	7.000	6.750	7.000	3.120	0.125	
W2070003500	7.000	6.750	7.000	3.500	0.125	
W2072500500	7.250	7.000	7.250	0.500	0.125	
W2072500625	7.250	7.000	7.250	0.625	0.125	
W2072500750	7.250	7.000	7.250	0.750	0.125	
W2072501000	7.250	7.000	7.250	1.000	0.125	
W2072501375	7.250	7.000	7.250	1.375	0.125	
W2072502000	7.250	7.000	7.250	2.000	0.125	
W2072507140	7.250	7.000	7.250	7.140	0.125	
W2073750750	7.375	7.125	7.375	0.750	0.125	
W2075000500	7.500	7.250	7.500	0.500	0.125	
W2075000625	7.500	7.250	7.500	0.625	0.125	
W2075000750	7.500	7.250	7.500	0.750	0.125	
W2075001000	7.500	7.250	7.500	1.000	0.125	
W2075001500	7.500	7.250	7.500	1.500	0.125	
W2075002000	7.500	7.250	7.500	2.000	0.125	
W2075002370	7.500	7.250	7.500	2.370	0.125	
W2075002500	7.500	7.250	7.500	2.500	0.125	
W2075002950	7.500	7.250	7.500	2.950	0.125	
W2077500500	7.750	7.500	7.750	0.500	0.125	
W2077500625	7.750	7.500	7.750	0.625	0.125	
W2077501000	7.750	7.500	7.750	1.000	0.125	
W2077501500	7.750	7.500	7.750	1.500	0.125	
W2077501620	7.750	7.500	7.750	1.620	0.125	
W2077502000	7.750	7.500	7.750	2.000	0.125	
W2077503500	7.750	7.500	7.750	3.500	0.125	
W2078751000	7.875	7.625	7.875	1.000	0.125	
W2080000180	8.000	7.750	8.000	0.180	0.125	
W2080000375	8.000	7.750	8.000	0.375	0.125	
W2080000500	8.000	7.750	8.000	0.500	0.125	
W2080000625	8.000	7.750	8.000	0.625	0.125	
W2080000750	8.000	7.750	8.000	0.750	0.125	
W2080000875	8.000	7.750	8.000	0.875	0.125	
W2080001000	8.000	7.750	8.000	1.000	0.125	
W2080001250	8.000	7.750	8.000	1.250	0.125	
W2080001460	8.000	7.750	8.000	1.460	0.125	
W2080001500	8.000	7.750	8.000	1.500	0.125	
W2080002000	8.000	7.750	8.000	2.000	0.125	
W2080002250	8.000	7.750	8.000	2.250	0.125	
W2080002945	8.000	7.750	8.000	2.945	0.125	
W2080005000	8.000	7.750	8.000	5.000	0.125	
W2082500500	8.250	8.000	8.250	0.500	0.125	
W2082500625	8.250	8.000	8.250	0.625	0.125	
W2082500750	8.250	8.000	8.250	0.750	0.125	
W2082501000	8.250	8.000	8.250	1.000	0.125	
W2082501250	8.250	8.000	8.250	1.250	0.125	
W2082501500	8.250	8.000	8.250	1.500	0.125	
W2082501750	8.250	8.000	8.250	1.750	0.125	

NOTE: MINIMUM LINE ORDER MAY APPLY